arXiv:1107.0989v2 [cs.DM] 9 Jul 2011

Geometry of Complex Networks and Structural Centrality

Gyan Ranjan[1,*], Zhi-Li Zhang

Dept. of Computer Science, University of Minnesota, Twin Cities, USA.

Abstract

We explore the geometry of complex networks in terms of an n-dimensional Euclidean embedding represented by the Moore-Penrose pseudo-inverse of the graph Laplacian ($\mathbf{L}^+$). The squared distance of a node i to the origin in this n-dimensional space (l^+_{ii}), yields a structural centrality index ($\mathcal{C}^*(i) = 1/l^+_{ii}$) for node i. In turn, the sum of reciprocals of individual node structural centralities, $\sum_i 1/\mathcal{C}^*(i) = \sum_i l^+_{ii}$, i.e. the trace of $\mathbf{L}^+$, yields the well-known Kirchoff index ($\mathcal{K}$), an overall structural descriptor for the network. In addition to this geometric interpretation, we provide alternative interpretations of the proposed indices to reveal their true topological characteristics: first, in terms of forced detour overheads and frequency of recurrences in random walks that has an interesting analogy to voltage distributions in the equivalent electrical network; and then as the average connectedness of i in all the bi-partitions of the graph. These interpretations respectively help establish the structural centrality ($\mathcal{C}^*(i)$) as a measure of both the overall position as well as the overall connectedness of node i in the network which in turn reflects the robustness of node i to random multiple edge failures. Through empirical evaluations using synthetic and real world networks, we demonstrate how the structural centrality is better able to distinguish nodes in terms of their structural roles in the network and, along with Kirchoff index, is appropriately sensitive to perturbations/rewirings in the network.

---

1. Introduction

Unlike traditional studies on network robustness, that typically treat networks as combinatoric objects and rely primarily on classical graph-theoretic concepts (e.g. minimum cuts), we explore a geometric approach which enables us to employ more advanced theories and techniques. More importantly, such an approach helps quantify and compare robustness of different nodes in the same network as well as different networks of comparable sizes, in terms of their local and global structures.

In this work, we study a geometric embedding of networks using the Moore-Penrose (pseudo) inverse of the graph Laplacian for the network, denoted henceforth by $\mathbf{L}^+$. We show that the diagonal entries of $\mathbf{L}^+$, denoted as l^+_{ii} for node i, that represent the squared distance of each node to the origin in the $n-dimensional$ Euclidean space of the network embedding, provide a robust measure of a node's structural centrality, given as $\mathcal{C}^*(i) = 1/l^+_{ii}$. In particular, closer a node i is to the origin in this space, more structurally central it is. Moreover, the trace of $\mathbf{L}^+$, $Tr(\mathbf{L}^+) = \sum_i 1/\mathcal{C}^*(i)$, yields the *Kirchoff index* ($\mathcal{K}$), a structural descriptor for the network as a whole. Once again, lower the value of $\mathcal{K}$ for a network, more compact the embedding, and more structurally robust the overall network is.

In addition to the geometric interpretation of structural centrality and Kirchoff index described above, we provide three alternative interpretations which respectively show how $\mathcal{C}^*(i)$ quantifies the overall position and connectedness of a node i, and therefore its robustness to failures in the network. We describe each of these separately below.

---

[*] Corresponding author.

Email addresses: `granjan@cs.umn.edu` (Gyan Ranjan), `zhzhang@cs.umn.edu` (Zhi-Li Zhang)

First, we equate structural centrality of a node i, i.e. $\mathcal{C}^*(i)$, to the (reciprocal of) average detour overhead incurred when a random walk between any source destination pair is forced to go through node i. Intuitively, the average overhead incurred in such detours (measured in terms of the number of steps in the random walk) will be lower if node i is structurally central (higher $\mathcal{C}^*(i)$ and lower l^+_{ii}) and vice versa.

Secondly, we show how $\mathcal{C}^*(i)$ is related to electrical voltages when the network is treated as an equivalent electrical network (EEN). This, in turn, yields an interpretation of $\mathcal{C}^*(i)$ in terms of the probability with which a random detour through i returns to the source node; referred to as the phenomenon of *recurrence* in random walk literature. More precisely, higher $\mathcal{C}^*(i)$ implies that a random detour through node i forces the random walk between any source destination pair to return to the source node with lower probability, thereby incurring lower detour overhead. Both of these interpretations, namely average detour overhead and probability of recurrence, show how $\mathcal{C}^*(i)$ quantifies the overall position of node i in the network.

Last but not the least, we establish how $\mathcal{C}^*(i)$ captures the overall connectedness of node i. To do so, we equate it to the number of nodes that i can communicate with when a sub-set of edges in the network fail in such a way that the network is partitioned into two connected sub-networks. A higher value of $\mathcal{C}^*(i)$, implies that i is present in the larger of the two sub-networks, on an average, resulting from such partitioning. In other words, $\mathcal{C}^*(i)$ reflects the immunity/vulnerability of node i towards multiple edge failures in the network, a distinct topological characteristic.

Through numerical simulations using synthetic and realistic network topologies, we demonstrate that our new indices better characterize robustness of nodes in network, both in terms of position as well as connectedness, as compared to other existing metrics (e.g. node centrality measured based on degree, shortest paths, etc.). A rank-order of nodes in terms of their structural centralities helps distinguish them in terms of their structural roles (such as core, gateway, etc.). Also, structural centrality and Kirchoff index, are both appropriately sensitive to local perturbations in the network, a property not displayed by other centralities in literature (as shown later in this paper).

The rest of the paper is organized as follows: we begin by providing a brief overview of several structural indices, characterizing node centrality as well as overall descriptors for networks, found in literature in §2. §3 introduces a geometric embedding of the network using the eigen-space of $\mathbf{L}^+$, structural centrality and Kirchoff index as measures of robustness. §4 demonstrates how structural centrality of a node reflects the average detour overhead in random walks through a particular node in question followed by its equivalence to the probability of recurrence. In §5 we show how structural centrality captures the average connectedness of nodes in the bi-partitions of a network. §6 presents comparative empirical analysis and in §7 the paper is concluded.

2. Related Work

Robustness of nodes to failures in complex networks is dependent on their overall *position* and *connectedness* in the network. Several centralities, that characterize position and/or connectedness of nodes in complex networks in different ways, have therefore been proposed in literature. Perhaps the simplest of all is degree — the number of edges incident on a node. Degree is essentially a *local* measure i.e. a first oder/one-hop connectedness index. A second-order variant called *joint-degree*, given by the product of degrees of a pair of nodes that are connected by an edge in the network, is also in vogue. However, except in *scale free* networks that display the so called *rich club connectivity* [2, 10, 11], neither degree nor joint-degree determine the overall position or the connectedness of nodes.

A class of structural indices called *betweennesses*, namely shortest path/geodesic (GB) [15, 16], flow (FB) [17] and random-walk (RB) [22] betweenness respectively quantify the positions of nodes, with respect to source destination pairs in the network. Betweennesses reflect the role played by a node in the communication between other nodes and are not the measures of a node's own connectedness.

A more sophisticated measure is geodesic closeness (GC)[15, 16]. It is defined as the (reciprocal of) average shortest-path distance of a node from all other nodes in the network. Clearly, geodesic closeness is a

p^{th}-order measure of connectedness where $p = \{1, 2, ..., \delta\}$, δ being the geodesic diameter of the graph, and is better suited for characterizing global connectedness properties than the aforementioned indices. However, communication in networks is not always confined to shortest paths alone and GC being geodesic based, ignores other alternative paths between nodes, however competitive they might be, and thus only partially captures connectedness of nodes. Some all paths based counterparts of geodesic closeness include information centrality [26] and random-walk centrality [24], that use random-walk based approach to measure centrality.

Recently, subgraph centrality (SC) — the number of subgraphs of a graph that a node participates in — has also been proposed [9]. In principle, a node with high subgraph centrality, should be better connected to other nodes in the network through redundant paths. Alas, subgraph centrality is computationally intractable and the proposed index in [9] approximates subgraph centrality by the sum of lengths of all *closed* walks, weighed in inverse proportions by the factorial of their lengths. This inevitably results in greater correlation with node degrees as each edge contributes to closed random-walks of lengths $2, 4, 6, ...$ and thus introduces local connectivity bias. In a subsequent paper, Estrada et al introduce the concept of vibrations to measure node vulnerability in complex networks [8]. Their index called *node displacement* bears significant resemblance to information centrality and has interesting analogies to physical systems. However, once again the true topological significance of the centrality measure, in terms of connectedness is wanting.

Our aim in this work, therefore, is to provide an index for robustness of nodes in complex networks, that effectively reflects both the position and connectedness properties of nodes and consequently, by extension, of the overall network.

3. Geometric Embedding of Networks using $\mathbf{L}^+$ and Structural Centrality

In studying the *geometry* of networks, we first need to embed a network (e.g. represented abstractly as a graph) into an appropriate geometric space endowed with a metric function (mathematically, a metric space). In this section we describe an n-dimensional embedding of the complex network using, the Moore-Penrose pseudo-inverse of the combinatorial laplacian ($\mathbf{L}^+$). The squared length of the position vector for a node in this space yields a geometric measure of centrality for the node while the sum of the squared lengths of the position vectors of all nodes, or the trace of $\mathbf{L}^+$, yields an overall robustness index for the graph. But first we need to introduce some basic notations.

Given a complex network, its topology is in general represented as a (weighted) graph, $G = (V, E, W)$, where $V(G)$ is the set of nodes representing, say, switches, routers or end systems in the network; $E = \{e_{uv} : u, v \in V\}$ is the set of edges connecting pairs of nodes representing, for example, the (physical or logical) communication links between the pair of nodes; and $W = w_{uv} \in \Re^+ : e_{uv} \in E(G)$ is a set of weights assigned to each edge of the graph (here $\Re^+$ denotes the set of nonnegative real numbers). These weights can be used to represent, for example, the capacity, latency, or geographical distance, or an (administrative) routing cost associated with the edge (communication link) e_{uv}. Note that if w_{uv} is simply 0 or 1, we have a simple and unweighted graph.

Given $G = (V, E, W)$, we introduce an $n \times n$ *affinity* matrix $\mathbf{A} = [a_{ij}]$ associated with G, where $n = |V(G)|$ is the number of nodes in G (the *order* of G), and $a_{ij} \geq 0$ is some function of the weight w_{ij}. For a simple graph where $w_{ij} \in \{0, 1\}$, setting $a_{ij} = w_{ij}$ yields the standard adjacency matrix of the graph G. In general, each entry a_{ij} captures some measure of affinity between nodes i and j: the larger a_{ij} is, nodes i and j are in a sense *closer* or more *strongly connected*. Hence in general, we refer to $\mathbf{A}$ as an affinity matrix associated with G. We assume that $a_{ij} = a_{ji}$, i.e. $\mathbf{A}$ is symmetric. For $1 \leq i \leq n$, define $d(i) = \sum_j a_{ij}$, and refer to $d(i)$ as the (generalized) degree of node i. (Note that if G is a simple unweighted graph j and $\mathbf{A}$ is its adjacency matrix, then $d(i)$ is the degree of node i.)

The *combinatorial Laplacian* of $\mathbf{A}$ (or the associated graph G), is defined as $\mathbf{L} = \mathbf{D} - \mathbf{A}$, where $\mathbf{D} = [d_{ii}] = d(i)$ is a diagonal matrix with $d(i)$'s on the diagonal. The Laplacian is a positive semidefinite matrix, and thus has n non-negative Eigen values λ_i's. For $1 \leq i \leq n$, let $\mathbf{u}_i$ be the corresponding eigenvector of λ_i such that $||\mathbf{u}_i||_2^2 = \mathbf{u}_i'\mathbf{u}_i$. We assume that the eigenvalues λ_i's are ordered such that $\lambda_1 \geq ... \geq \lambda_n = 0$. Then the matrix formed by the corresponding eigenvectors $\mathbf{u}_i's$, $\mathbf{U} = [\mathbf{u}_1, ..., \mathbf{u}_n]$, is orthogonal i.e. $\mathbf{U}'\mathbf{U} = \mathbf{I}$, the identity matrix. More importantly, $\mathbf{L}$ admits an eigen decomposition $\mathbf{L} = \mathbf{U}\Lambda\mathbf{U}'$, where Λ is the diagonal matrix $\Lambda = [\lambda_{ii}] = \lambda_i$.

Like $\mathbf{L}$, its Moore-Penrose (pseudo) inverse $\mathbf{L}^+$ is also positive semi-definite, and admits an eigen decomposition of the form, $\mathbf{L}^+ = \mathbf{U}\Lambda^+\mathbf{U}'$, where $\mathbf{\Lambda}^+$ is a diagonal matrix consisting of λ^{-1} if $\lambda_i > 0$, and 0 if $\lambda_i = 0$ (for simplicity of notation, in the following we will use the convention $\lambda_i^{-1} = 0$ if $\lambda_i = 0$). Define $\mathbf{X} = \Lambda^{+1/2}\mathbf{U}'$. Hence, $\mathbf{L}^+ = \mathbf{X}'\mathbf{X}$ which means that the network can be embedded into the Euclidean space $\Re^n$ where the coordinates of node i are given by $\mathbf{x}_i$, the i^{th} column of $\mathbf{X}$. As the centroid of the position vectors lies at the origin in this n-dimensional space [14], the squared distance of node i from the origin is exactly the corresponding diagonal entry of $\mathbf{L}^+$ i.e. $||\mathbf{x}_i||_2^2 = l_{ii}^+$ and the squared distance between two nodes $i, j \in V(G), ||\mathbf{x}_i - \mathbf{x}_j||_2^2 = Vol(G)^{-1}C_{ij}$ where $Vol(G) = \sum_{i=1}^n d(i)$ is called the *volume* of the graph (a constant for the graph) and C_{ij} is called the *commute time* defined as the expected length of commute in a random walk between i and j in the network [4].

Based on the geometric embedding of the graph using $\mathbf{L}^+$ described above, we now put forth two robustness metrics. First, a rank order for individual nodes in terms of their relative robustness called *structural centrality*, defined as:

Definition 1. *Structural centrality of node $i \in V(G)$:*

$$\mathcal{C}^*(i) = 1/l_{ii}^+, \quad \forall i \in V(G) \tag{1}$$

Specifically, closer a node is to the origin in this n-dimensional space, more structurally central it is and consequently greater its robustness (as shown later). Next, a structural descriptor for the overall robustness of the network called *Kirchoff index*, defined as:

Definition 2. *Kirchoff index for $G(V, E)$:*

$$\mathcal{K}(G) = Tr(\mathbf{L}^+) = \sum_{i=1}^{n} l_{ii}^+ = \sum_{i=1}^{n} 1/\mathcal{C}^*(i) \tag{2}$$

Geometrically, more compact the embedding is, lower the value of $\mathcal{K}(G)$ and more robust the network G is. It is worth pointing out that Kirchoff index has been used to model molecular strengths in the theoretical chemistry literature [29], primarily because it has interesting analogies in the field of electrical networks but its true topological significance has scarcely been explored previously. Also, since

$$\mathcal{K}(G) = Tr(\mathbf{L}^+) = \sum_{i=1}^{n-1} \frac{1}{\lambda_i} \tag{3}$$

Kirchoff index can be thought of as a more generalized version of the much celebrated *algebraic connectivity* of the graph, measured by the second smallest eigen-value of the Laplacian i.e. λ_{n-1} [12, 13]. We can therefore use Kirchoff index to compare the robustness of two graphs with the same order and volume.

In what follows, we demonstrate how these two metrics indeed reflect robustness of nodes and the overall graph respectively, first through rigorous mathematical analysis resulting in closed form representations and then with empirical evaluations over realistic network topologies.

4. Structural Centrality, Random Walks and Electrical Voltages

To show that structural centrality ($\mathcal{C}^*(i)$) indeed captures the overall position of a node, we relate it to the lengths of random-walks on the graph. In §4.1, we demonstrate how $\mathcal{C}^*(i)$ is related to the average overhead incurred in random *detours* through node i as a *transit* vertex. Next in §4.2, we provide an electrical interpretation for it in terms of voltages and the probability with which a random detour through node i returns to the source node.

4.1. Detours in Random Walks

A simple random walk $(i \rightarrow j)$, is a discrete stochastic process that starts at a node i, the source, visits other nodes in the graph G and stops on reaching the destination j [18]. In contrast, we define a *random detour* as:

Definition 3. *Random Detour* $(i \rightarrow k \rightarrow j)$*: A random walk starting from a source node* i*, that must visit a transit node* k*, before it reaches the destination* j *and stops.*

Effectively, such a random detour is a combination of two simple random walks: $(i \rightarrow k)$ followed by $(k \rightarrow j)$. We quantify the difference between the random detour $(i \rightarrow k \rightarrow j)$ and the simple random walk $(i \rightarrow j)$ in terms of the number of steps required to complete each of the two processes given by hitting time.

Definition 4. *Hitting Time* (H_{ij})*: The expected number of steps in a random walk starting at node* i *before it reaches node* j *for the first time.*

Clearly, $H_{ik} + H_{kj}$ is the expected number of steps in the random detour $(i \rightarrow k \rightarrow j)$. Therefore, the overhead incurred is:

$$\Delta H^{i \rightarrow k \rightarrow j} = H_{ik} + H_{kj} - H_{ij} \tag{4}$$

Intuitively, more peripheral transit k is, greater the overhead in (4). The overall peripherality of k is captured by the following average:

$$\Delta H^{(k)} = \frac{1}{n^2 \; Vol(G)} \sum_{i=1}^{n} \sum_{j=1}^{n} \Delta H^{i \rightarrow k \rightarrow j} \tag{5}$$

Alas, hitting time is not a Euclidean distance as $H_{ij} \neq H_{ji}$ in general. An alternative is to use commute time $C_{ij} = H_{ij} + H_{ji} = C_{ji}$, a metric, instead. More importantly [20],

$$C_{ij} = Vol(G)(l^+_{ii} + l^+_{jj} - l^+_{ij} - l^+_{ji}) \tag{6}$$

and in the overhead form (4), (non-metric) hitting and (metric) commute times are in fact equivalent (see propositions 9 – 58 in [19]):

$$\Delta H^{i \rightarrow k \rightarrow j} = (C_{ik} + C_{kj} - C_{ij})/2 = \Delta H^{j \rightarrow k \rightarrow i} \tag{7}$$

We now exploit this equivalence to equate the cumulative detour overhead through transit k from (5) to l^+_{kk} in the following theorem.

Theorem 1.

$$\Delta H^{(k)} = l^+_{kk} \tag{8}$$

Proof: Using $\Delta H^{i \rightarrow k \rightarrow j} = (C_{ik} + C_{kj} - C_{ij})/2$:

$$\Delta H^{(k)} \quad = \quad \frac{1}{2n^2 \; Vol(G)} \sum_{i=1}^{n} \sum_{j=1}^{n} C_{ik} + C_{kj} - C_{ij}$$

Observing $C_{xy} = Vol(G) \; (l^+_{xx} + l^+_{yy} - 2l^+_{xy})$ [20] and that $\mathbf{L}^+$ is doubly centered (all rows and columns sum to 0) [14], we obtain the proof.

□

Therefore, a low value of $\Delta H^{(k)}$ implies higher $\mathcal{C}^*(k)$ and more structurally central node k is in the network. Theorem 1 is interesting for several reasons. First and foremost, note that:

$$\sum_{j=1}^{n} C_{kj} = Vol(G) \; (n \; l^+_{kk} + Tr(\mathbf{L}^+)) \tag{9}$$



Figure 1: A simple graph G and its EEN.

As $Tr(\mathbf{L}^{+})$ is a constant for a given graph and an invariant with respect to the set $V(G)$, we obtain $l^{+}_{kk} \propto \sum_{j=1}^{n} C_{kj}$; lower l^{+}_{kk} or equivalently higher $\mathcal{C}^{*}(k)$, implies shorter average commute times between k and the rest of the nodes in the graph on an average. Moreover,

$$\mathcal{K}(G) = Tr(\mathbf{L}^{+}) = \sum_{k=1}^{n} l^{+}_{kk} = \frac{1}{2nVol(G)} \sum_{k=1}^{n}\sum_{j=1}^{n} C_{kj} \tag{10}$$

As $\mathcal{K}(G)$ reflects the average commute time between any pair of nodes in the network, it is a measure of overall connectedness in G. For two networks of the same order (n) and volume ($Vol(G)$), the one with lower $\mathcal{K}(G)$ is better connected on an average.

4.2. Recurrence, Voltage and Electrical Networks

Interestingly, the detour overhead in (4) is related to *recurrence* in random walks — the expected number of times a random walk ($i \to j$) returns to the source i [7]. We now explore how recurrence in detours related to structural centrality of nodes. But first we need to introduce some terminology.

The equivalent electrical network (EEN) [7] for $G(V, E, W)$ is formed by replacing an edge $e_{ij} \in E(G)$ with a resistance equal to w_{ij}^{-1} (see Fig. 1). The *effective resistance* (Ω_{ij}) is defined as the voltage developed across a pair of terminals i and j when a unit current is injected at i and is extracted from j, or vice versa. In the EEN, let V_k^{ij} be the voltage of node k when a unit current is injected at i and a unit current is extracted from j. From [27], $U_k^{ij} = d(k)V_k^{ij}$. Substituting $k = i$ we get, $U_i^{ij} = d(i)V_i^{ij}$; the expected number of times a random walk ($i \to j$) returns to the source i. For a finite graph G, $U_i^{ij} > 0$. The following theorem connects recurrence to the detour overhead.

Theorem 2.

$$\begin{aligned}\Delta H^{i \to k \to j} &= \frac{Vol(G)\ (U_i^{ik} + U_i^{kj} - U_i^{ij})}{d(i)} \\ &= Vol(G)\ (V_i^{ik} + V_i^{kj} - V_i^{ij})\end{aligned}$$

Proof: From [27] we have, $\Delta H^{i \to k \to j} = d(i)^{-1}\ Vol(G)\ U_i^{jk}$. The rest of this proof follows by proving $U_i^{jk} = U_i^{ik} + U_i^{kj} - U_i^{ij}$.

From the *superposition principle* of electrical current, we have $V_x^{xz} = V_y^{xz} + V_y^{zx}$. Therefore,

$$\begin{aligned}V_i^{ik} + V_i^{kj} - V_i^{ij} &= V_j^{ik} + V_j^{ki} + V_i^{kj} - V_k^{ij} + V_k^{ji} \\ &= V_j^{ik} + (V_j^{ki} + V_i^{kj} - V_k^{ij} - V_k^{ji})\end{aligned}$$

From the *reciprocity principle*, $V_z^{xy} = V_x^{zy}$. Therefore, $V_i^{ik} + V_i^{kj} - V_i^{ij} = V_i^{jk}$. Multiplying by $d(i)$ on both sides we obtain the proof.

□



(a) Partition $P = (S, S')$ (b) Spn. forest in $P = (S, S')$

Figure 2: Partitions and spanning forests of a graph.

The term $(U_i^{ik} + U_i^{kj}) - U_i^{ij}$ can be interpreted as the expected extra number of times a random walk returns to the source i in the random detour $(i \to k \to j)$ as compared to the simple random walk $(i \to j)$. Each instance of the random process that returns to the source, must effectively start all over again. Therefore, more often the walk returns to the source greater the expected number of steps required to complete the process and less central the transit k is, with respect to the source-destination pair (i, j).

Therefore, $\Delta H^{(k)}$, that is the average of $\Delta H^{i\to k\to j}$ over all source destination pairs, tells us the average increase in recurrence caused by node k in random detours between any source destination pair in the network. Higher the increase in recurrence, i.e. $\Delta H^{(k)}$, lower the magnitude of $\mathcal{C}^*(k)$ and less structurally central the node k is in the network.

5. Connected Bi-Partitions of a Network

Having established, that nodes with higher $\mathcal{C}^*(i)$, are more structurally central in the network, we now turn to average connectedness of nodes in this section. To show how structural centralities of nodes capture their immunity/vulnerability to random failures in the network, we study their connectedness in all the bi-partitions of a graph.

Definition 5. *Bi-partition* $(P = (S, S'))$*: A cut of the graph* G *which contains exactly two mutually exclusive and exhaustive connected subgraphs* S *and* S'.

Let, $V(S)$ and $V(S')$ be the mutually exclusive and exhaustive subsets of $V(G)$, $E(S)$ and $E(S')$, the sets of edges in the respective components S and S' of P and $E(S, S')$, the set of edges that violate P i.e. have one end in S and the other in S'. Also, let $\mathcal{T}(S)$ and $\mathcal{T}(S')$ be the set of spanning trees in the respective component sets S and S'. We denote by $\mathcal{P}(G)$, the set of all bi-partitions of $G(V, E)$. Clearly, a given $P = (S, S')$ represents a state of the network in which $E(S, S')$ have failed. A node $i \in V(S)$ stays connected to $|V(S)| - 1$ nodes and gets disconnected from $|V(S')|$ nodes. In the following relationship we show how structural centrality of node i is related to a weighted sum of $|V(S)'|$ over all the bi-partitions $P \in \mathcal{P}(G)$ of the network.

Theorem 3.

$$l_{ii}^+ \propto \sum_{P \in \mathcal{P}(G)}^{i \in V(S)} |\mathcal{T}(S)||\mathcal{T}(S')||V(S')| \tag{11}$$

Proof sketch: The following result, due to Chebotarev et al. [5, 6], forms the basis of our proof. Let $\mathcal{F}_x$ be the set of spanning rooted forests of $G(V, E)$ with x edges. Precisely, $F_x \in \mathcal{F}_x$, is a spanning acyclic subgraph of G with the same node set as G and is composed of exactly $n - x$ trees with one node marked as a *root* in each of these x trees. Let $\mathcal{F}_x^{ii}$, be the subset of $\mathcal{F}_x$ in which node i is the root of the tree in which it belongs. Then,

$$l_{ii}^+ = \frac{\varepsilon(\mathcal{F}_{n-2}^{ii}) - \frac{1}{n}\varepsilon(\mathcal{F}_{n-2})}{\varepsilon(\mathcal{F}_{n-1})} \tag{12}$$

Here, $\varepsilon(\cdot)$ simply represents the cardinality of the input set (see [5, 6] for details). Clearly, $\varepsilon(\mathcal{F}_{n-2})$ and $\varepsilon(\mathcal{F}_{n-1})$ are invariants over the set of vertices $V(G)$ for a given graph. Hence, $l^+_{ii} \propto \varepsilon(\mathcal{F}^{ii}_{n-2})$. The rest of the proof follows from the results of the following lemmas:

Lemma 1. *Let $\mathcal{F}^{ii}_{n-2|P}$ be the set of spanning forests with $n-2$ edges (or exactly two trees) rooted at node i in a given bi-partition $P = (S, S')$ and $\mathcal{T}_S$, $\mathcal{T}_{S'}$ be the set of spanning trees in S and S' respectively. If $i \in V(S)$ then,*

$$\varepsilon(\mathcal{F}^{ii}_{n-2|P}) = |\mathcal{T}_S|\ |\mathcal{T}_{S'}|\ |V(S')|$$

Proof : Let $T_1 \in \mathcal{T}_S$ and $T_2 \in \mathcal{T}_{S'}$. Clearly, $|E(T_1)| = |V(S)| - 1$ and $|E(T_2)| = |V(S')| - 1$. As $|V(S)| + |V(S')| = |V(G)|$ and $|E(T_1) \cap E(T_2)| = 0$, $|E(T_1) \cup E(T_2)| = |V(S)| - 1 + |V(S')| - 1 = n - 2$. Each such pair (T_1, T_2) is a spanning forest of $n-2$ edges. Given i is the root of T_1 in S, we can choose $|V(S')|$ roots for T_2 in S'. There being $|\mathcal{T}_S|\ |\mathcal{T}_{S'}|$ such pairs: $\varepsilon(\mathcal{F}^{ii}_{n-2|P}) = |\mathcal{T}_S|\ |\mathcal{T}_{S'}|\ |V(S')|$.

□

By symmetry, for $j \in V(S')$:

$$\varepsilon(\mathcal{F}^{jj}_{n-2|P}) = |\mathcal{T}_S|\ |\mathcal{T}_{S'}|\ |V(S)|$$

Lemma 2. *Given $\mathcal{P}(G)$, the set of all bi-partitions of G:*

$$\varepsilon(\mathcal{F}^{ii}_{n-2}) = \sum_{P \in \mathcal{P}(G)}^{i \in V(S)} |\mathcal{T}(S)||\mathcal{T}(S')||V(S')|$$

Proof: By definition, $\forall F \in \mathcal{F}_{n-2}$, F belongs to exactly one of the partitions of G. Hence, $\mathcal{F}^{ii}_{n-2} = \coprod_{P \in \mathcal{P}} \varepsilon(\mathcal{F}^{ii}_{n-2|P})$. As the RHS is a disjoint union, counting members on both sides we obtain the proof.

□

Evidently, combining the results of the two lemmas above, we obtain the proof for Theorem 3.

□

To paraphrase, given a bi-partition $P = (S, S') \in \mathcal{P}(G)$, such that $i \in V(S)$ and $j \in |V(S')|$, Lemma 1 yields: $\varepsilon(\mathcal{F}^{ii}_{n-2|P})/\varepsilon(\mathcal{F}^{jj}_{n-2|P}) = |V(S')|/|V(S)|$. Clearly, for a given bi-partition, nodes in the larger of the two components of P have a lower number of spanning forests rooted at them than those in the smaller component and vice versa. By extension,

$$l^+_{ii} - l^+_{jj} \quad \propto \quad \sum_{P \in \mathcal{P}(G)}^{i \in V(S), j \in V(S')} |\mathcal{T}(S)||\mathcal{T}(S')|(|V(S')| - |V(S)|)$$

can be interpreted as a comparative measure of connectedness of nodes i and j. Note that for $P \in \mathcal{P}(G)$, the RHS of (13) is zero when nodes i and j belong to the same component of P or if $|V(S)| = |V(S')|$ and positive when $i \in V(S), j \in V(S')$ and $|V(S')| > |V(S)|$ or vice versa. Therefore, a node i with higher structural centrality stays connected to a greater number of nodes on an average in a disconnected network, than one with lower structural centrality and is consequently more immune to random edge failures in the network.

By simple extension, Kirchoff index represents the average connectedness of all the nodes when a failure of a subset of edges partitions the network into two halves, thereby truly reflecting overall network robustness. It is easy to demonstrate that of all trees of order n, the star has the lowest Kirchoff index and the root of the star has highest $\mathcal{C}^*(i)$ value. Also, amongst all graphs of order n with differing volumes, the completely connected graph K_n has the lowest Kirchoff index.



(a) Abilene Topology (b) Simulated topology (c) Perturbations

Figure 3: Abilene Network and a simulated topology.

6. Empirical Evaluations

We now empirically study the properties of structural centrality ($\mathcal{C}^*(i)$) and Kirchoff index (we use $\mathcal{K}^* = \mathcal{K}^{-1}$ henceforth to maintain *higher is better*). We first show in §6.1, how a rank-order of nodes in terms of their structural centralities captures their structural roles in the network and then in §6.2 demonstrate how it, along with Kirchoff index, is appropriately sensitivity to rewirings and local perturbations in the network.

6.1. Identifying Structural Roles of Nodes

Consider the router level topology of the Abilene network (Fig. 3(a)) [1]. At the core of this topology, is a ring of 11 POP's, spread across mainland US, through which several networks interconnect. Clearly, the connectedness of such a network is dependent heavily on the low degree nodes on the ring. For illustration, we mimic the Abilene topology, with a simulated network (Fig. 3(b)) which has a 4-node core $\{v_1, ..., v_4\}$ that connects 10 networks through gateway nodes $\{v_5, ..., v_{14}\}$ (Fig.3(b)).

Fig. 4 shows the (max-normalized) values of geodesic closeness (GC), subgraph centrality (SC) and structural centrality $\mathcal{C}^*$ for the core $\{v_1, ..., v_4\}$, gateway $\{v_5, ..., v_{14}\}$ and other nodes $\{v_{15}, ..., v_{65}\}$ in topology (Fig.3(b)). Notice that v_5 and v_6, two of the gateway nodes in the topology, have the highest values of degree in the network i.e. $(d(v_5) = d(v_6) = 10)$ while v_{14} has the highest subgraph centrality (SC). In contrast, $\mathcal{C}^*(i)$ ranks the four core nodes higher than all the gateway nodes with v_1 at the top. The relative peripherality of v_5, v_6 and v_{14} as compared to the core nodes requires no elaboration. As far as geodesic centrality (GC) is concerned, it ranks all the nodes in the subnetwork abstracted by v_5, namely $v_{15} - v_{23}$, as equals even though v_{22} and v_{23} have redundant connectivity to the network through each other and are, ever so slightly, better connected than the others - a property reflected in their $\mathcal{C}^*(i)$ rankings.

We see similar characterization of structural roles of nodes in two real world networks in terms of structural centrality: the western states power-grid network [28] and a social network of co-authorships [23], as shown through a color scheme based on $\mathcal{C}^*(i)$ values in Fig. 5. Core-nodes connecting different sub-communities of nodes in both these real world networks are recognized effectively by structural centrality as being more central (*Red* end of the spectrum) than several higher degree peripheral nodes.



Figure 4: Max-normalized centralities for simulated topology.

6.2. Sensitivity to Local Perturbations

An important property of centrality measures is their sensitivity to perturbations in network structure. Traditionally, structural properties in real world networks have been equated to average statistical properties like power-law/scale-free degree distributions and rich club connectivity [2, 10, 11]. However, the same degree sequence $D = \{d(1) \geq d(2) \geq ... \geq d(n)\}$, can result in graphs of significantly varying topologies. Let $\mathcal{G}(D)$ be the set of all connected graphs with scaling sequence D. The generalized Randic index $R_1(G)$ [3, 25]:

$$R_1(G) = \sum_{e_{ij} \in E(G)} d(i)d(j) \tag{13}$$

where $G \in \mathcal{G}(D)$, is considered to be a measure of overall connectedness of G. Higher $R_1(G)$ suggests that nodes of higher degrees connect with each other with high probability thereby displaying the so-called *rich club connectivity* (RCC) in G [21]. Similarly, the average of each centrality/betweenness index (GC, SC, GB, RB averaged over the set of nodes), is in itself a global structural descriptor for the graph G [9]. We now examine the sensitivity of each index with respect to local perturbations in the subnetwork abstracted by the core node v_1 and its two gateway neighbors v_5 and v_6.

First, we rewire edges $e_{15,5}$ and $e_{6,1}$ to $e_{15,1}$ and $e_{6,5}$ respectively (PERT-I Fig. 3(c)). PERT-I is a degree preserving rewiring which only alters local connectivities i.e. neither individual node degrees nor average node degree changes. Fig. 6(a) and Fig. 7 respectively show the altered values of centralities ($\mathcal{C}^*, GC, SC$) and betweennesses, geodesic and random-walk i.e. (GB, RB), after PERT-I. Note, after PERT-I, v_{15} is directly connected to v_1 which makes $\mathcal{C}^*(v_{15})$ comparable to other gateway nodes while $SC(v_{15}), GB(v_{15}), RB(v_{15})$ seem to be entirely unaffected. Moreover, PERT-I also results in v_6 losing its direct link to the core, reflected in the decrease in $\mathcal{C}^*(v_6)$ and a corresponding increase in $\mathcal{C}^*(v_5)$. $\mathcal{C}^*(i)$, however, still ranks the core nodes higher than v_5 (whereas SC, GB, RB do not) because PERT-I being a local perturbation should not affect nodes outside the sub-network — v_1 continues to abstract the same sub-networks from the rest of the topology. We, therefore, observe that $\mathcal{C}^*(i)$ is appropriately sensitive to the changes in connectedness of nodes in the event of local perturbations. But what about the network on a whole?

Let G and G_1 be the topologies before and after PERT-I. G_1 is less well connected overall than G as the failure of $e_{5,1}$ in G_1 disconnects 19 nodes from the rest of the network as compared to 10 nodes in G.



(a) The western-states power grid network [28] (b) A network of co-authorships in network sciences [23]

Figure 5: Real world networks: $Red \rightarrow Turqoise$ in order of decreasing $\mathcal{C}^*(i)$.



(a) After PERT-I (b) After PERT-II

Figure 6: Max-normalized values of structural centrality, geodesic closeness and subgraph centrality for core, gateway and some other nodes.

However,

$$\Delta R_1(G \rightarrow G_1) = \frac{R_1(G_1) - R_1(G)}{R_1(G)} = 0.029$$

as the two highest degree nodes (v_5 and v_6) are directly connected in G_1 (see TABLE 1 for the sensitivity of other centrality based global structural descriptors). In contrast, $\Delta\mathcal{K}^*(G \rightarrow G_1) = -0.045$, which rightly reflects the depreciation in overall connectedness after PERT-I (recall $\mathcal{K}^*(G) = \mathcal{K}^{-1}(G)$. Table 1 shows the changes in the average of all centrality and betweenness indices post PERT-I.

A subsequent degree preserving perturbation PERT-II of G_1, rewiring $e_{22,23}$ and $e_{24,25}$ to $e_{22,25}$ and $e_{23,24}$, to obtain G_2, creates two cycles in G_2 that safeguard against the failure of edge $e_{5,6}$. This significantly improves local connectivities in the sub-network. However, $\Delta R_1(G_1 \rightarrow G_2) = 0$ (and average SC decreases) while $\Delta\mathcal{K}^*(G_1 \rightarrow G_2) = 0.036$ which once again shows the efficacy of Kirchoff index as a measure of global connectedness of networks.



Figure 7: After PERT-I: Max-normalized values of structural centrality, geodesic and random-walk betweennesses for core, gateway and some other nodes.

Table 1: Sensitivity to local perturbations, $\overline{X} = 1/n \sum_i^n X(i)$: Avg. node centrality for a network.

#	Structural Descriptor	PERT-I	PERT-II
1	$\mathcal{K}^*(G)$ (or $\overline{\mathcal{C}^*}$)	↓	↑
2	$R_1(G)$	↑	↔
3	$\overline{GC}$	↓	↑
4	$\overline{SC}$, $\overline{GB}$	↑	↓
5	$\overline{RB}$	↑	↑

7. Conclusion and Future Work

In this work, we presented a geometric perspective on robustness in complex networks in terms of the Moore-Penrose pseudo-inverse of the graph Laplacian. We proposed structural centrality ($\mathcal{C}^*(i)$) and Kirchoff index ($\mathcal{K}(G)$) that respectively reflect the length of the position vector for a node and the overall volume of the graph embedding and therefore are suitable geometric measures of robustness of individual nodes and the overall network. Additionally, we provided interpretations for these indices in terms of the overhead incurred in random detours through a node in question as well as in terms of the recurrence probabilities and voltage distribution in the EEN corresponding to the network. Both indices reflect the global connectedness properties of individual nodes and the network on a whole, particularly in the event of multiple edge failures that may render the network disconnected. Through numerical analysis on simulated and real world networks, we demonstrated that $\mathcal{C}^*(i)$ captures structural roles played by nodes in networks and, along with Kirchoff index, is suitably sensitive to perturbations/rewirings in the network. In terms of computational complexity, structural centrality compares well with other geodesic and all-paths based indices in literature (see Table 2) and performs better than random-walk betweenness in the asymptotic case. In future, we aim at investigating similar metrics for the case of strongly connected weighted directed graphs to further generalize our work.

8. Acknowledgment

This research was supported in part by DTRA grant HDTRA1-09-1-0050 and NSF grants CNS-0905037, CNS-1017647 and CNS-1017092.

Table 2: Taxonomy and computational complexities of centrality measures (for all nodes).

#	Measure	Paths covered	Complexity
1.	Degree	-	$O(m)$
2.	GC, GB	Geodesic paths	$O(n^3)$
3.	$\mathcal{C}^*$	All paths	$O(n^3)$
4.	SC	All paths	$O(n^3)$
5.	RWB	All paths	$O(m+n)n^2$
6.	FB	All paths	$O(m^2n)$

References

[1] www.stanford.edu/services/internet2/abilene.html.

[2] R. Albert, H. Jeong, and A. L. Barábasi. Error and attack tolerance of complex networks. *Nature*, 406(6794):378–382, 2000.

[3] B. Bollobas and P. Erdos. Graphs of extremal weights. *Ars Combin.*, 50:225–233, 1998.

[4] A. K. Chandra, P. Raghavan, W. L. Ruzzo, R. Smolensky, and P. Tiwari. The electrical resistance of a graph captures its commute and cover times. In *Proc. of Annual ACM Symposium on Theory of Computing*, pages 574–586, 1989.

[5] P. Chebotarev and E. Shamis. The matrix-forest theorem and measuring relations in small social groups. *Automation and Remote Control*, 58(9):1505–1514, 1997.

[6] P. Chebotarev and E. Shamis. On proximity measures for graph vertices. *Automation and Remote Control*, 59(10):1443–1459, 1998.

[7] P. G. Doyle and J. L. Snell. *Random Walks and Electric Networks.* The Math. Assoc. of America, 1984.

[8] E. Estrada and N. Hatano. A vibrational approach to node centrality and vulnerability. *Physica A*, 389, 2010.

[9] E. Estrada and J. A. Rodríguez-Velázquez. Subgraph centrality in complex networks. *Phys. Review E*, 71, 2005.

[10] M. Faloutsos, P. Faloutsos, and C. Faloutsos. On power-law relationships of the internet topology. In *Proc. of the ACM SIGCOMM*, pages 251–262, 1999.

[11] I. J. Farkas, I. Derenyi, A. L. Barábasi, and T. Vicsek. Spectra of real world graphs: Beyond the semicircle law. *Physical Review E*, 64(2), 2001.

[12] M. Fiedler. Algebraic connectivity of graphs. *Czechoslovak Math. J.*, 23:298–305, 1973.

[13] M. Fiedler. A property of eigenvectors of nonnegative symmetric matrices and its applications to graph theory. *Czechoslovak Math. J.*, 25(100):619–633, 1975.

[14] F. Fouss, A. Pirotte, J. M. Renders, and M. Saerens. Random-walk computation of similarities between nodes of a graph with application to collaborative recommendation. *IEEE Transactions on Knowledge and Data Engineering*, 19, 2007.

[15] L. C. Freeman. A set of measures of centrality based upon betweenness. *Sociometry*, 40:35–41, 1977.

[16] L. C. Freeman. Centrality in social networks: Conceptual clarification. *Social Networks*, 1:215–239, 1979.

[17] L. C. Freeman, S. P. Borgatti, and D. R. White. Centrality in valued graphs: A measure of betweenness based on network flow. *Social Networks*, 13:141–154, 1991.

[18] F. Gobel and A. Jagers. Random walks on graphs. *Stochastic Processes and Their Applications*, 2:311–336, 1974.

[19] J. G. Kemeny, J. L. Snell, and A. W. Knapp. *Denumerable Markov Chains.* Van Nostrand, New York, 1966.

[20] D. J. Klein and M. Randic. Resistance distance. *J. Math. Chemistry*, 12:81–95, 1993.

[21] L. Li, D. Alderson, W. Willinger, and J. Doyle. A first-principles approach to understanding the internet's router-level topology. In *Proc. of the ACM SIGCOMM*, 2004.

[22] M. E. J. Newman. A measure of betweenness centrality based on random walks. *Social Networks*, 27(1):39–54, 2005.

[23] M. E. J. Newman. Finding community structure in networks using the eigenvectors of matrices. *Preprint Physics/0605087*, 2006.

[24] J. D. Noh and H. Rieger. Random walks on complex networks. *Phys. Rev. Lett.*, 92, 2004.

[25] M. Randic. On characterization of molecular branching. *J. Amer. Chem. Society*, 97:6609–6615, 1975.

[26] K. A. Stephenson and M. Zelen. Rethinking centrality: Methods and examples. *Social Networks*, 11:1–37, 1989.

[27] P. Tetali. Random walks and effective resistance of networks. *Journal of Theoretical Probability*, pages 101–109, 1991.

[28] D. J. Watts and S. H. Strogatz. Collective dynamics of 'small-world' networks. *Nature*, 393:440–442, 1998.

[29] W. Xiao and I. Gutman. Resistance distance and laplacian spectrum. *Theoretical Chemistry Accounts*, 110:284–289, 2003.